MANUAL TORQUE WRENCH

- The Torque Wrench is made of all-metal structure, which is more durable
- The ratchet head can be switched clockwise or counterclockwise, and the ratchet has 45 teeth
- Accuracy: ± 3% of the reading value (the accuracy of 500 Nm and above is ± 4% of the reading value)
- Each torque wrench has a unique identification code for easy traceability.
- The permanent torque scale on the alloy steel is easy for users to read and compare with the metric and imperial systems.
- Pull down the locking ring on the handle, turn the handle to adjust the torque and push it up to lock the torque valve
- There are anti-slip grooves on the handle, which are comfortable and anti-slip.



Model No	Square Drive	Range (NM)	Range (Ft.Lb)	Length (mm)	Width (mm)	Weight (kg)
TM45	1/2″	10 – 60	9 – 45	388	38	0.96
TM75	1/2″	20 – 100	15 -75	443	38	1.04
TM90	1/2″	25 – 125	20 – 90	443	38	1.04
TM150	1/2″	40 – 200	30 – 150	468	40	1.16
TM150L	1/2″	40 – 200	30 – 150	525	40	1.29
TM250	1/2″	65 - 335	50 - 250	528	40	1.30
TM250L	3/4″	65 – 335	50 – 250	700	40	2.15
TM300	3/4″	80 – 400	60 – 300	710	57	3.00
TM400	3/4″	100 – 500	80 – 400	710	57	3.00
TM400L	3/4″	100 – 500	80 – 400	855	60	5.00
TM600	3/4″	160 – 800	120 – 600	1055	60	5.90
TM600A	1″	160 – 800	120 – 600	1055	60	5.90
TM750	3/4″	200 – 1000	150 – 750	1055	60	5.90
TM750A	1″	200 – 1000	150 – 750	1055	60	5.90
TM1100	1″	300 – 1500	200 – 1100	1260	75	9.20
TM1500	1″	400 – 2000	300 – 1500	1260	75	9.20
TM2000	1″	600 - 3000	400 – 2000	1260	75	10.5
TM1100L	1″	300 – 1500	200 – 1100	1600	75	13.00
TM1500L	1″	400 – 2000	300 – 1500	1600	75	13.00
TM2000L	1″	600 - 3000	400 – 2000	1840	75	15.2
TM1100E	1″	300 – 1500	200 – 1100	2200	75	11.5
TM1500E	1″	400 – 2000	300 – 1500	2200	75	11.5
TM2000E	1″	600 - 3000	400 – 2000	2780	75	15.5

MANUAL TORQUE WRENCH

- The Torque Wrench is made of all-metal structure, which is more durable
- Accuracy: ± 3% of the reading value (the accuracy of 500 Nm and above is ± 4% of the reading value)
- Each torque wrench has a unique identification code for easy traceability.
- The permanent torque scale on the alloy steel is easy for users to read and compare with the metric and imperial systems.
- Pull down the locking ring on the handle, turn the handle to adjust the torque and push it up to lock the torque valve
- There are anti-slip grooves on the handle, which are comfortable and anti-slip.



Model No	Square	Range (NM)	Range (Ft.Lb)	Length (mm)	Width (mm)	Weight (kg)
TMH45	9 x 12	10 – 60	9 – 45	375	38	0.86
TMH75	9 x 12	20 – 100	15 – 75	430	38	0.94
TMH90	9 x 12	25 – 125	20 – 90	430	38	0.94
TMH150	14 x 18	40 – 200	30 – 150	467	38	1.06
TMH250	14 x 18	65 – 335	50 – 250	527	38	1.20
TMH250L	14 x 18	65 – 335	50 – 250	700	38	2.00
TMH300	14 x 18	80 – 400	60 – 300	700	38	2.00
TMH400S	24 x 32	100 – 500	80 – 400	710	56	3.00
TMH400	24 x 32	100 – 500	80 – 400	855	56	5.00
TMH600	24 x 32	160 – 800	120 – 600	1055	56	5.90
TMH750	24 x 32	200 – 1000	150 – 750	1055	56	5.90
TMH1100	27 x 36	300 – 1500	200 – 1100	1249	64	9.00
TMH1500	27 x 36	400 – 2000	300 – 1500	1249	64	9.00
TMH2000	27 x 36	600 – 3000	400 – 2000	1249	64	10.3
TMH1100E	27 x 36	300 – 1500	200 – 1100	2200	64	12.5
TMH1500E	27 x 36	400 – 2000	300 – 1500	2200	64	12.5
TMH2000E	27 x 36	600 – 3000	400 – 2000	2780	64	15.3
Model No	**Square**	**Range (NM)**	**Range (Ft.Lb)**	**Length (mm)**	**Width (mm)**	**Weight (kg)**
TMR45	φ16	10 – 60	9 – 45	377	38	0.86
TMR90	φ16	25 – 125	20 – 90	431	38	0.94
TMR150	φ16	40 – 200	30 – 150	455	38	1.06
TMR250	φ16	65 – 335	50 – 250	515	38	1.20
TMR250L	φ16	65 – 335	50 – 250	695	38	2.00
TMR300	φ16	80 – 400	60 – 300	695	38	2.00
TMR400	φ22	100 – 500	80 – 400	800	38	4.30
TMR600	φ22	160 – 800	120 – 600	1005	38	5.20
TMR750	φ22	200 - 1000	150 - 750	1005	38	5.20